

Application No. 10/816,488
Response to Office Action

Customer No. 01933

Amendments to the Specification:

Please amend the paragraph at page 17, line 24 to page 18, line 17 as follows:

The cab roof member 10F of the seventh embodiment is formed as a single piece in which an iron plate 16a is formed on the top face (outer surface) 20 side, whereas the leather-like sheet 21 (e.g., "PEF" produced by Toray Industries, Inc.) is formed on the ceiling face 17 side, and another iron plate is included as the reinforcing member 16 between the foam serving as the base material layer 11 and the inner face of the sound absorbing layer 19. In the cab roof member 10F having the above structure, the top face 20 is constituted by the iron plate 16a, another iron plate is inserted as the reinforcing material 16 and, moreover, the sound absorbing layer 19 is provided. Therefore, the iron plate 16a is exposed at the ceiling top face side, functioning as a reinforcing material as well as a sound insulator whereas the internally disposed reinforcing material 16 exerts strength maintaining and sound insulating effects, so that further improvements can be expected. In addition, the ceiling face 17 is constituted by the

Application No. 10/816,488
Response to Office Action

Customer No. 01933

leather-like sheet material 21 so that a beautiful interior which gives a soft impression can be achieved. The sound absorbing layer 19 further gives a sound absorbing effect in addition to the sound insulation achieved by the iron plates 16, 16a and gives a cushioning effect to withstand external force working from the ceiling face 17 side.